

COMBUSTIBLE GAS DETECTOR

TECHNICAL DATA

FEATURES

- Detects a wide variety of gases, including some toxic gases and nuisance vapors
- Following is a partial list of the more common gases detected: Natural Gas; Propane; Butane; Methane; Acetone; Alcohol; Ammonia; Steam; Carbon Monoxide; Gasoline; Jet Fuel; Hydrogen Sulfide; Smoke; Industrial Solvents; Lacquer Thinner; Naphtha
- Precision semi-conductor sensor detects even the smallest leaks
- Audible (variable tick rate) and visible indications help to pinpoint leak sources
- Adjustable sensitivity helps to eliminate background gas concentrations in contaminated environments
- Includes batteries and earplugs for noisy environments

SPECIFICATIONS

Sensitivity: 50 ppm methane

Response Time: < 2 seconds

Alarm Limit: At 10% LEL for methane (can be calibrated for other concentrations or gases up to 40% LEL)

Power Supply: 3 x "C" batteries

Battery Life: 8 hours of continuous use

Probe Length: 16" gooseneck



ORDERING INFORMATION

GD-3300 Combustible Gas Detector
TGS2611-COO Replacement Sensor Tip
CERTIGM1 NIST Calibration Certificate
GD-3300-NIST Gas Detector & NIST