

THERMOCOUPLE THERMOMETER

TECHNICAL DATA



FEATURES

- Single input thermocouple thermometer designed for field use
- Display maximum reading plus Data Hold
- Large LCD display with backlight
- User selectable °C, °F or °Kelvin
- User selectable resolution of 0.1 or 1°C (0.1 or 1°F)
- Includes 9V battery, holster and **TP-01** bead probe
- Accepts K-type thermocouple probes (sold separately)
- **MODEL ST-610BDELUXE:** Thermometer Kit includes **ST-610B** Thermocouple Thermometer, **LS-109** Surface Probe, **LS-103** Air/Gas Probe, **LS-107** General-purpose Probe, all in a hard carrying case

SPECIFICATIONS

Temperature Range: -58 to 2000°F (-50 to 1300°C)
Resolution: 0.1°F or 1°F (0.1°C or 1°C)
Accuracy: ±(0.5% of reading + 2°F/1°C)
Power Supply: Single 9V battery
Dimensions: 165 x 76 x 73mm
Weight: 403g



ORDERING INFORMATION

ST-610B Thermocouple Thermometer
ST-610B-NIST T/C Thermometer & NIST
ST-610BDELUXE Thermometer Kit
LS-103 Air/Gas Probe
LS-104 Right Angle Surface Probe
LS-107 General Purpose Probe
LS-109 Surface Probe
LS-134A Needle Tip Probe
LS-139 Surface Probe
BS-6 Tripod
CERTITM1 NIST Calibration Certificate

1-877-849-2127 | info@reedinstruments.com

www.reedinstruments.com