


Dial Snap Gage

SERIES 201

FEATURES

- Designed for quick GO/NG judgment of diameters of cylinders and shafts in machining processes.
- Dial indicator is optional.
- Anvil retracting stroke: 2mm/.078"
- Anvil positioning range: 25mm/1"
- Wide (13.5 x 12mm/1.53 x .47"), flat carbide anvils.
- Both front edges of the anvil are chamfered for easy workpiece insertion.



201-101
with optional dial indicator

Technical Data

Accuracy: Refer to the list of specifications
 Anvil retracting stroke: 2mm/.078"
 Anvil positioning range: 25mm/1"
 Anvil flatness: 1µm/.00004"

SPECIFICATIONS

Metric

Range	Order No.	Parallelism	Measuring force	Recommended dial indicator (optional)
0 - 25mm	201-101	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
25 - 50mm	201-102	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
50 - 75mm	201-103	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
75 - 100mm	201-104	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
100 - 125mm	201-105	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
125 - 150mm	201-106	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
150 - 175mm	201-107	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
175 - 200mm	201-108	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
200 - 225mm	201-109	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
225 - 250mm	201-110	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
250 - 275mm	201-111	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)
275 - 300mm	201-112	5µm	15N±3N	2046SB (0.01mm reading), 2109SB-10 (0.001mm reading)

Inch

Range	Order No.	Parallelism	Measuring force	Recommended dial indicator (optional)
0 - 1"	201-151	.0002"	15N±3N	2803SB-10 (.0001" reading)
1 - 2"	201-152	.0002"	15N±3N	2803SB-10 (.0001" reading)
2 - 3"	201-153	.0002"	15N±3N	2803SB-10 (.0001" reading)
3 - 4"	201-154	.0002"	15N±3N	2803SB-10 (.0001" reading)
4 - 5"	201-155	.0002"	15N±3N	2803SB-10 (.0001" reading)
5 - 6"	201-156	.0002"	15N±3N	2803SB-10 (.0001" reading)
6 - 7"	201-157	.0002"	15N±3N	2803SB-10 (.0001" reading)
7 - 8"	201-158	.0002"	15N±3N	2803SB-10 (.0001" reading)
8 - 9"	201-159	.0002"	15N±3N	2803SB-10 (.0001" reading)
9 - 10"	201-160	.0002"	15N±3N	2803SB-10 (.0001" reading)
10 - 11"	201-161	.0002"	15N±3N	2803SB-10 (.0001" reading)
11 - 12"	201-162	.0002"	15N±3N	2803SB-10 (.0001" reading)

DIMENSIONS

